



**TURBO POWER**  
**SYNTHETIC MOTOR OIL**  
**SAE 5W-30    API SN/CF**  
**SAE 10W-40    API SN/CF**

ESN Synthetic Motor Oil formulated using high quality synthetic oil component combination with superior additives package. ESN Synthetic Motor Oil resists breakdown under high loads, temperatures and speeds experienced by today's high speed, high-torque engines.

**APPLICATIONS / BENEFITS :**

- \* Affords maximum bearing protection.
- \* Provides excellent piston ring sealing.
- \* Maximizes obtainable engine horsepower.
- \* Protects against rust and corrosion.

**PERFORMANCE STANDARD :**

- \* API SN/CF
- \* ACEA A2-96#2, A3-98, B2-98, B3-98, E2-96#2
- \* VW 500/501/505
- \* BMW special oil
- \* Porsche "All Seasons Engine Oil"
- \* Mercedes-Benz 228.1, 229.1

**TYPICAL CHARACTERISTICS :**

TEST DESCRIPTION	METHOD	TYPICAL RESULTS	
SAE Viscosity Grade	SAE J 300	5W-30	5W-40
Specific Gravity @ 15 °C	ASTM D 4052	0.866	0.872
Flash Point, °C	ASTM D 92	212	215
Pour Point, °C	ASTM D 97	-36	-33
Kinematic Viscosity @ 40°C	ASTM D 445	90.6	101.3
	ASTM D 445	14.4	14.8
Viscosity Index	ASTM D 2270	165	152
TBN, (mgKOH/g)	ASTM D 2896	8.0	11
Color	ASTM D 1500	2.0	< 3.5

**ESIONAL SDN. BHD.** (876294-T)

No. 21-2, Jalan Apollo CG U5/CG, Bandar Pinggiran Subang, Seksyen U5, 40150 Shah Alam, Selangor Darul Ehsan, Malaysia. | Tel : 603-7846 2108/603-7846 2109 | Fax : 603-7842 2107 | Email : marketing@esional.com | Web : www.esional.com | Copyright 2013-Esional Sdn. Bhd. , All rights reserved. All specifications are subject to change without prior notice. Please contact our sales team for latest information of our products and services.